

ECOLINE

SINGLE COLOUR LED BATTEN

GBT503



FEATURES

- Slim steel body
- Powder coated finish
- Opal polycarbonate diffuser
- Constant current LED driver fitted
- Large terminal block installed
- LED lifespan: 50000 Hours @L70, Ta 25°C
- Ta: -20°C to +40°C




EMERGENCY

- Intelligent automatic recharging function
- Constant current mode
- 3 hour emergency operation
- Over discharge protection
- LED charge status display
- Test switch with self-test function
- Ta: 0 to +40°C



DIMENSION



TECHNICAL DATA

Rated supply voltage	230V~	Recharge hours	16h
Frequency	50/60Hz	EM LED power LED	2.3W
Input power	3.5W	Battery type	LiFePO4 3.2V 3.3Ah

CLASSIFICATION: C0: D50, C90:D32 (120) / C0: D40, C90:D32 (150)

TECHNICAL SPECIFICATIONS

MODEL NO.	INPUT VOLTAGE (V)	POWER (W)	LUMEN (lm)	COLOUR TEMPERATURE (K)	CRI	BEAM ANGLE (°)	DIMENSIONS (L×W×H) (mm)	FITTING COLOUR	CARTON QUANTITY
GBT503/60 CW	230	20	2200	4000	>80	120	615 x 71 x 76	White	6
GBT503/120 CW	230	40	4400	4000	>80	120	1221 x 71 x 76	White	6
GBT503/120 DL	230	40	4400	5700	>80	120	1221 x 71 x 76	White	6
GBT503/150 CW	230	60	6600	4000	>80	120	1523 x 71 x 76	White	6
GBT503/150 DL	230	60	6600	5700	>80	120	1523 x 71 x 76	White	6
GBT503/120 BC EM	230	40 (2.3)*	4400 (340)*	4000/5700	>80	120	1221 x 71 x 76	White	6
GBT503/150 BC EM	230	60 (2.3)*	6600 (340)*	4000/5700	>80	120	1523 x 71 x 76	White	6

*When running on EM backup Wattage is 2.3w & Lumen 340lm

Specifications above are for reference only and may vary without prior notice